

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 March 2005 (24.03.2005)

PCT

(10) International Publication Number
WO 2005/026665 A2

(51) International Patent Classification⁷: **G01F 1/00**

(21) International Application Number:
PCT/EP2004/010733

(22) International Filing Date:
15 September 2004 (15.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/503,616 15 September 2003 (15.09.2003) US

(71) Applicant (for all designated States except US): **DIAGNOSWISS S.A.** [CH/CH]; Rte de l'Île-au-Bois 2, c/o Cimo S.A., Case Postale, CH-1870 Monthey (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ROSSIER, Joël** Stephane [CH/CH]; Ch. des Ravines 13, CH-1895 Vionnaz (CH). **MORIER, Patrick** [CH/CH]; Ch. des Baisemens 7, CH-1807 Blonay (CH). **REYMOND, Frédéric** [CH/CH]; Rte de Corsy 23, CH-1093 La Conversion (CH).


(74) Agent: **HANSON, William, Bennett**; Bromhead Johnson, Kingsbourne House, 229-231 High Holborn, London WC1V 7DP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MICROFLUIDIC FLOW MONITORING DEVICE



(57) Abstract: An electrochemical flow monitoring device comprises a microfluidic system comprising at least one covered microchannel (3) having an inlet (4) and an outlet (5). A pressure difference is applied between the inlet and the outlet of the microfluidic system, for example by changing the relative heights of the inlet (4) and outlet (5), such as to generate a flow of solution within the microchannel (3). The microfluidic system has at least one electrode (8) for monitoring said flow of solution by measuring an electrochemical property of said solution.



Declaration under Rule 4.17:

- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.